

N 70, TELESCOPIC COOKER HOOD, 60 CM, STAINLESS STEEL D46ML54N1B



A



Optional accessories

Z54TS02X0	Standard recirculation kit
Z54TH60D1	Design Handle strip
Z54TL60X0	Lowering frame
Z51TB2X4	Clean Air Standard odor filter (repl.)
Z51TD1X1	Long Life recirculation kit external
Z51TI2X4	Clean Air Standard recirculation kit
Z51TP0X0	Long Life odor filter (replacement)
Z51XB1X6	Clean Air Plus odor filter (replacement)
Z51XC1X6	Clean Air Plus recirc. kit external
Z54TC02X0	Standard odor filter (replacement)

Telescopic hood: designed to provide powerful extraction without impacting on your kitchen space or design. These hoods pull out from underneath a cabinet when required for a streamlined kitchen.

- ✓ Efficient Drive Motor – Quiet and energy-efficient hood motor for a calmer kitchen.
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ Dimmer Function – easily dim the light according to your mood with the touch of a button
- ✓ Interval Ventilation – automatically ventilates every hour for crisp, clean air
- ✓ Automatic After-running – ventilation continues for several minutes after you turn it off

Features

Technical Data

Typology:	Pull-out
Length of electrical supply cord:	175.0 cm
Min. required niche size for installation (HxWxD):	385mm x 524.0mm x 290mm mm
Minimum distance above an electric hob:	430 mm
Minimum distance above a gas hob:	650 mm
Net weight:	11.4 kg
Type of control:	Electronic
Number of speed settings:	3-stage + 2 intensive
Maximum output air extraction:	392 m³/h
Boost position output recirculating:	628 m³/h
Maximum output recirculating air:	358 m³/h
Boost position air extraction:	717 m³/h
Number of lights (Stck):	2
Noise level:	53 dB(A) re 1 pW
Diameter of air outlet:	120 / 150 mm
Grease filter material:	Washable stainless steel
EAN code:	4242004251132
Connection rating:	144 W
Fuse protection:	10 A
Voltage:	220-240 V
Frequency:	50; 60 Hz
Plug type:	GB plug
Installation type:	Built-in
Delay Shut off modes:	10 min



4 242004 251132

N 70, TELESCOPIC COOKER HOOD, 60 CM, STAINLESS STEEL D46ML54N1B

Features

Features

- Soft touch control with 7 segment LED display
- 3 power levels and 2 intensive settings
- SoftLight with dimmer function
- 2 x 1,5W LED
- Efficient BLDC technology
- Noise reduction function
- Interval operation
- Automatic intensive revert (6mins)
- Automatic after running (Automatic after running (10 minutes))
- 2 metal grease filter cassettes
- Saturation indicator for grease filter

Design

- 60 cm wide
- Stainless steel
- Handle strip specification: stainless steel with logo
- Steel filter cover

Performance

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use: 392 m³/h
 - Intensive: 717 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 53 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
 - Max. normal use: 53 dB(A) re 1 pW
 - Intensive: 68 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
 - Extraction rate in recirculation mode: Max. normal use: 358 m³/h
 - Intensive: 628 m³/h
 - Noise level in recirculation mode: Max. normal use: 60 dB(A) re 1 pW
 - Intensive: 71 dB(A) re 1 pW
- Colour Temperature: 3500 K
- Light Intensity: 294 lux
- Average Energy Consumption: 37.8 kWh/year*
- Power rating: 144 W
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*

Planning and installation information

- Installation system: Telescopic comfort installat.
- Installation: Cupboard 60 cm

- Dimensions (HxWxD): 426 x 598 x 290 mm
- Built-in dimensions (HxWxD): 385 x 524 x 290 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Electrical cable length 1.75 m

* In accordance with the EU-Regulation No 65/2014

N 70, TELESCOPIC COOKER HOOD, 60 CM,
STAINLESS STEEL
D46ML54N1B

Dimensioned drawings



