

N 90, Wall-mounted cooker hood, 90 cm, Stainless steel
D96BMU5N5B




COOKING PASSION SINCE 1877



The coordinating and stylish Neff box hood is modern in design and keeps up with your cooking.

- ✓ Fully Automatic Hood – Takes control as soon as you switch on the hob.
- ✓ Cooktop-based Hood Control – Adjust your hood's extraction level and lighting.
- ✓ Adjustable LED White Colour Temperature – easily adjust the light to the shade that's right for your kitchen
- ✓ Special Noise Insulation – For a quiet cooking area.
- ✓ Efficient Drive Motor – Quiet and energy-efficient hood motor for a calmer kitchen.



Features

Technical Data

Typology : Wall-mounted
 Length of electrical supply cord : 130.0 cm
 Height of the chimney : 582-908/568-1018 mm
 Height of the appliance : 46 mm
 Minimum distance above an electric hob : 550 mm
 Minimum distance above a gas hob : 650 mm
 Net weight : 19.1 kg
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction : 430 m³/h
 Boost position output recirculating : 457 m³/h
 Maximum output recirculating air : 353 m³/h
 Boost position air extraction : 844 m³/h
 Number of lights (Stck) : 3
 Noise level : 55 dB(A) re 1 pW
 Diameter of air outlet : 120 / 150 mm
 Grease filter material : Washable stainless steel
 EAN code : 4242004234944
 Connection rating : 169 W
 Fuse protection : 10 A
 Voltage : 220-240 V
 Frequency : 50; 60 Hz
 Plug type : GB plug
 Installation type : Wall-mounted
 Delay Shut off modes : 10M min

Optional accessories

Z51CBI2X4	Clean Air Standard recirculation kit
Z51CXC2N6	Clean Air Plus recirc. kit external
Z51CXI1X6	Clean Air Plus recirculation kit
Z51FXJ0X5	Long Life recirculation kit
Z53XXB1X6	Clean Air Plus odor filter (replacement)
Z5895N0	Stainless steel back panel 900 mm
Z5906N1	Chimney extension 1000 mm
Z5916N1	Chimney extension 1500 mm



N 90, Wall-mounted cooker hood, 90 cm, Stainless steel
D96BMU5N5B



COOKING PASSION SINCE 1877

Features

Key performance features:

- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 430 m³/h
Intensive 844 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 55 dB dB*

Special features

- Climate Control Sensor
- Hob-Hood control (with Wi-Fi enabled hob)
- Remote Monitoring and Control for connected home appliances and operation via smartphone or tablet (only in countries where Home Connect service is available)
- The Home Connect functionality can be extended by integrating numerous applications from external cooperation partners (partnerships)
- Voice Control enabled via popular voice assistants (only in countries where this service is available)
- Adjustable color temperature (2.700 K - 5.000 K) for adaption to the room lighting available via Home Connect
- Fully automatic hood

Features

- Touch control
- 3 power levels and 2 intensive settings
- 3 x 3W LED lights
- softLight with dimmer function
- Efficient BLDC-technology
- Interval operation
- Automatic after running (Automatic after running (10 minutes))
- Automatic intensive revert (6mins)
- 3 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- Noise reduction function
- Additional noise insulation
- easy to clean Inner frame

Design

- Chimney hood
- Installation: wall
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 max. 844 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 55 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 55 dB(A) re 1 pW
Intensive: 69 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 55 dB (A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
Extraction rate in recirculation mode: Max. normal use: 353 m³/h
Intensive: 457 m³/h
Noise level in recirculation mode: Max. normal use: 67 dB(A) re 1 pW
Intensive: 71 dB(A) re 1 pW
- Power rating: 169 W
- Light Intensity: 578 lux
- Electrical cable length 1.3 m
- Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 614-954 x 898 x 500 mm
- Dimensions recirculating (HxWxD): 614-1064 x 898 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD): 795-1139 x 898 x 500 mm
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 33.5 kWh/year*

Optional accessories

- Recirculating kit Z50XXPOX0

* In accordance with the EU-Regulation No 65/2014

N 90, Wall-mounted cooker hood, 90 cm, Stainless steel
D96BMU5N5B

Dimensioned drawings

