

N 50, Built-under freezer, 82 x 59.8 cm, flat hinge  
G4344XFF0G



COOKING PASSION SINCE 1877



The built-in freezer with temperature rise alarm and superfreeze function.

✓ Super Freeze – Lowers the temperature temporarily to prevent frozen goods from warming up by new arrivals in the freezer

#### Features

##### Technical Data

Energy Efficiency Class : F  
Average annual energy consumption in kilowatt hour per year (kWh/a) : 224 kWh/a  
Sum of volume of frozen compartments : 106 l  
Airborne acoustical noise emissions : 38 dB(A) re 1 pW  
Airborne acoustical noise emission class : C  
Thermometer freeze section : Analog  
Light : No  
Product category : Upright freezer  
Construction type : Built-in  
Door panel options : Possible but accessory  
Frost free system : No  
Height of the appliance : 820 mm  
Width of the appliance : 598 mm  
Depth of the product : 548 mm  
Dimensions of the packed product (HxWxD) : 890 x 620 x 670 mm  
Net weight : 36.7 kg  
Gross weight : 39.6 kg  
Connection rating : 90 W  
Fuse protection : 13 A  
Frequency : 50 Hz  
Length of electrical supply cord : 230.0 cm  
Door hinge : Right reversible  
Defrost process : manual  
Warning signal / malfunction : visual and audible  
Door lock : No  
Number of drawers/baskets (Stck) : 3  
Number of freezing flaps (Stck) : 0  
EAN code : 4242004237693  
Brand : Neff  
Product name / Commercial code : G4344XFF0G  
Product category : Upright freezer  
Included accessories : 1 x ice cube tray



4 242004 237693

N 50, Built-under freezer, 82 x 59.8 cm, flat hinge  
G4344XFFOG



COOKING PASSION SINCE 1877

## Features

### Functions

- Fully Integrated

### Design features

- Mechanical control
- Temperature indicator on inside of door
- 1 compressor/1 cold circuit
- SuperFreeze function with automatic deactivation
- Freezer malfunction warning signal: Optic and acoustic Warning System

### Key features - Freezer section

- 3 freezer drawers
- 1 ice cube tray with lid
- Right hinged door, reversible
- Ventilation through plinth
- Variable plinth adaption
- Height adjustable feet in the front
- Connection value 90 W
- 220 - 240 V

### Dimension and installation

- Dimensions: 82 cm H x 59.8 cm W x 54.8 cm D
- Niche Dimensions: 82 cm H x 60 cm W x 55 cm D
- G4344XFFOG

### Included accessories

- KU1213Z0

### Design features

### Dimension and installation

### Additional features

### Performance and Consumption


- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.
- EU19\_EEK\_D: F
- Total Volume : 106 l
- Net 4\* compartment volume : 106 l
- Freezing capacity 24h : 7.4 kg
- Annual Energy Consumption: 224 kWh/a
- Climate Class: SN-T
- Noise Level : 38 dB , EU19\_Noise emission class\_D: C
- Temperature rise time : EU19\_Temperature rise time\_D: 10 H

N 50, Built-under freezer, 82 x 59.8 cm, flat hinge  
G4344XFF0G

Dimensioned drawings




measurements in mm  
Recommended gap dimensions for flat hinges



	F	R	X
16-19	0-3	2.5	
	20	0-1	3
21	2-3	2.5	
	21	0-1	3
22	2-3	2.5	
	0	4	
	1	3.5	
	2-3	3	

The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units.



Maximal permissible weight of the unit fronts

Fitted unit fronts that exceed the permissible weight may cause damage and result in functional impairment of the hinges.

Δ: Weight

A: Appliance door height including hinges in mm

B: Undamped hinge, unit front in kg

C: Damped hinge, unit front in kg

D: Additional possible load in kg with heavy load kit

A	B	C	D
1500-1750	22	22	
720-1400	19	19	B+5 / C+5
A1	15	19	
A2	15	19	