

G 5350 SCVi Active Plus Fully integrated dishwashers for optimum drying results thanks to AutoOpen drying.



- Perfect results in less than one hour QuickPowerWash
- Save up to 50 % more electricity hot water connection
- Fresh water dishwashers from 6.0
 I litres in the Automatic programme
 d
- Versatile and secure comfort basket design
- Maximum versatility Heightadjustable upper basket



EAN: 4002516610403 / Material number: 12153390 / Old Material Number: 21535062GB

ninless Steel. ly integrated fascia ogramme selector buttor ligit 7-segment display hite mfortClose
ly integrated fascia ogramme selector buttor ligit 7-segment display lite
ly integrated fascia ogramme selector buttor ligit 7-segment display lite
ly integrated fascia ogramme selector buttor ligit 7-segment display lite
ly integrated fascia ogramme selector buttor ligit 7-segment display lite
ogramme selector buttor digit 7-segment display nite
digit 7-segment display nite
iite
mfortClose
mortologo
oustic
Dustic
.
)
'4
<u> </u>
.0
9
MultiFlex trav
MultiFlex tray



G 5350 SCVi Active Plus Fully integrated dishwashers for optimum drying results thanks to AutoOpen drying.




EAN: 4002516610403 / Material number: 12153390 / Old Material Number: 21535062GB

Number of place settings	14
Safety	
Waterproof system	•
Technical data	
Niche width minimal in mm	600
Niche width max in mm	600
Niche height minimal in mm	805
Niche height maximal in mm	870
Niche depth in mm	550
Appliance width in mm	598
Appliance height in mm	805
Appliance depth in mm	550
Depth with door open in cm	116.5
Net weight in kg	44.0
Total rated load in kW	2.00
Voltage in V	230
Fuse rating in A	10
Number of phases	1
Electrical frequency standard	50
Length of water inlet hose in m	1.50
Length of water drain hose in m	1.50
Length of supply lead in m	1.80
Min. front panel weight in kg	4.0
Max. front panel weight in kg	11.0
[can be retrofitted by Service to min.]	8.0
[can be retrofitted by Service to max.]	16.0



G 5350 SCVi Active Plus Fully integrated dishwashers for optimum drying results thanks to AutoOpen drying.



1) Plinth height 35-155 mm, 2) Plinth height 100-220 mm, 3) Appliance height max. 930 mm with plinth height conversion kit (Mat.-Nr. 6.394.761),