

N 70, GAS HOB, 75 CM, STAINLESS STEEL T27DS59N0





Optional accessories

Z32SW11X0 Wok ring
Z2480X0 Simmer plate
Z32SE10X0 Small pot support

The gas hob with a stainless-steel surface design and adjustable FlameSelect.

- $\sqrt{\text{FlameSelect}^{\text{@}}}$ Gain ultimate control of your flame.
- $\sqrt{\mbox{ Pan Supports}}$ continuous cast-iron pan supports for maximum stability and cooking convenience.
- $\sqrt{}$ Wok Burner powerful cooking at up to 4 kW.
- $\sqrt{}$ Sword Knobs a better feel and easier to operate, the new knob in an attractive design.
- $\sqrt{\,}$ Stainless steel surface elegant and sophisticated design.

Features

Technical Data Product name/family:gas hob w integrated controls Construction type: Built-in Type of control setting devices:sword knobs Min. required niche size for installation (HxWxD): .. 45 x 560-562 x 480-492 mm Dimensions of the packed product (HxWxD): . 145 x 793 x 597 mm Net weight: 14.1 kg Residual heat indicator:without Basic surface material: Stainless steel Color of surface:Stainless steel EAN code:4242004203506 Gas connection rating:11500 W



N 70, GAS HOB, 75 CM, STAINLESS STEEL T27DS59N0

Features

Design

- Stainless steel surface
- black cast iron pan supports with protective rubber feet

Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 burner hob
- Left front: Economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: Wok burner up to 4 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

Safety

• Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): $53 \times 750 \times 520$
- Required niche size for installation (HxWxD mm) : $45 \times 560 \times (480 492)$
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 11.5 KW



N 70, GAS HOB, 75 CM, STAINLESS STEEL T27DS59N0

5.

