

N 50, BUILT-IN DOUBLE OVEN U2GCH7AN0B





Optional accessories

Z11AB15A0 Baking tray, non-stick ceramic coated, Z11AU15A0 Universal pan, non-stick ceramic coated, Z11CR10X0 Baking and roasting grid (standard), Z11GT10X3 Glass roasting dish, 5,4l, Z11GU20X0 Glasspan, Z11TI15X0 Cliprails, Z12CB10A0 Baking tray, enamelled, Z12CL10A0 Lid for professional pan, enamelled, Z12CN10A0 Professional pan, enamelled, Z12CN10A0 Multipurpose pan, enamelled, Z13CR10X0 Baking and roasting grid (steam), Z1608BX0 Full ext rails, level independent, Z1650BE0 Half tray, Z1655CA0 Air Fry & Grill tray, Z1913X0 Baking Stone, Z19DD10X0 Steam set for ovens

Double built-in oven - perfect for grilling, baking and roasting of multiple dishes at the same time.

 $\sqrt{}$ Dual cleaning options: Pyrolytic cleaning programmes - just let the oven interior clean itself. EasyClean - the quick and easy option for day to day maintenance.

Features

Technical Data	Duil+ io
Construction type:	
Dimensions of the packed product (HxWxD): .	
Control Panel Material:	
Door Material:	
Net weight: Usable volume of cavity:	
Cooking method:	
CircoTherm® gentle, Hot Air, Conventional hea	
Bottom heat, Hot air grilling	it, Fizza Settilig,
Oven control:	electronic
Number of interior lights:	
EAN code:	
Energy efficiency rating:	
Energy consumption per cycle conventional (2)	
kWh/cycle	
Energy consumption per cycle forced air conve	ection
(2010/30/EC):	0.81 kWh/cycle
Energy efficiency class (2010/30/EC) - cavity 2	
Energy consumption per cycle conventional - c	
(2010/30/EC):	0.83 kWh/cycle
Energy efficiency index (2010/30/EC):	95.3 %
Energy efficiency index cavity 2 (2010/30/EC):	: 120.3 %
Connection rating:	6300 W
Fuse protection:	32 A
Voltage:	220-240 V
Frequency:	50 Hz
Plug type:	
(electrical connection by electrician), fixed connection	
Included accessories:3 x combination g	rid, 1 x universal pan





N 50, BUILT-IN DOUBLE OVEN U2GCH7AN0B

Features

- LCD-display control (white)
- Interior halogen light, On/off button

Features

- Door lock during pyrolytic cleaning
- Control panel lock Automatic safety switch off Residual heat indicator

Top oven additional features

- Cavity volume: 34 Litre
- Pyrolytic cleaning in upper oven
- Full glass inner door
- Cavity (inner surface) top: Enamel grey
- Door hinge small cavity: bottom

Main oven additional features

- Pyrolytic cleaning
- Full glass inner doors
- EasyClean
- Cavity (inner surface) bottom: enamel anthracite
- Door hinge big cavity: Drop down door
- Oven with 4 heating methods: Top/bottom heat, Full surface grill, Small area grill, Bottom heat
- \bullet Temperature range 30 °C 275 °C
- ullet 3 x combination grid, 1 x universal pan

Performance/technical information

- Nominal voltage: 220 240 V
- \bullet Appliance dimension (hxwxd): 888 mm x 594 mm x 550 mm
- Please refer to the dimensions provided in the installation manual



N 50, BUILT-IN DOUBLE OVEN U2GCH7AN0B

Dimensioned drawings measurements in mm **- 20** 18 ↓ 19.5 145

